

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Wilsonart® 110 Adhesive Solvent
Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Cleaning solvent for laminate

1.3. Details of the supplier of the safety data sheet

Wilsonart LLC
P.O. Box 6110
10501 NW H. K. Dodgen Loop
Temple, TX 76503
Information phone: 800-433-3222 (USA)

1.4. Emergency telephone number

Emergency number : CHEMTREC: (800) 424-9300
CHEMTREC (International): 703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Eye Irrit. 2A H319
Repr. 2 H361
STOT SE 3 H336
STOT RE 2 H373
Asp. Tox. 1 H304

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

Signal word (GHS-US) : **Danger**

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility. Suspected of damaging the unborn child

Wilsonart® 110 Adhesive SolventPrecautionary statements
(GHS-US)

H373 - May cause damage to organs through prolonged or repeated exposure

: P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, ventilating, lighting equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe mist, spray, vapours
P261 - Avoid breathing mist, spray, vapours
P264 - Wash hands, forearms and face thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, protective clothing, protective gloves
P301+P310 - IF SWALLOWED: Immediately call a doctor, a poison center
P302+P352 - If on skin: Wash with plenty of soap and water
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P312 - Call a doctor, a poison center if you feel unwell
P314 - Get medical advice/attention if you feel unwell
P321 - Specific treatment (see first aid instructions on this label)
P331 - Do NOT induce vomiting
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P370+P378 - In case of fire: Use alcohol resistant foam, dry extinguishing powder, carbon dioxide (CO₂) to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

Wilsonart® 110 Adhesive Solvent

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Distillates, petroleum, light distillate hydrotreating process, low-boiling	(CAS No) 68410-97-9	10 - 30
Acetone	(CAS No) 67-64-1	15 - 40
Toluene	(CAS No) 108-88-3	10 - 30
Cyclohexane	(CAS No) 110-82-7	7 - 13
Isopentane	(CAS No) 78-78-4	7 - 13
Pentane	(CAS No) 109-66-0	7 - 13
Naphtha, petroleum, hydrotreated light	(CAS No) 64742-49-0	1 - 5
Hexane	(CAS No) 110-54-3	1 - 5

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention. If breathing is difficult, supply oxygen. If breathing has stopped, give artificial respiration.
- First-aid measures after skin contact : IF ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. If irritation develops or persists, get medical attention.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. If pain, blinking, or irritation develops or persists, get medical attention. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention immediately.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation. Causes damage to organs through prolonged or repeated exposure. Suspected of damaging fertility. Suspected of damaging the unborn child.
- Symptoms/injuries after inhalation : May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : Causes skin irritation.

Wilsonart® 110 Adhesive Solvent

Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.
Chronic symptoms	: Causes damage to organs through prolonged or repeated exposure. Suspected of damaging fertility. Suspected of damaging the unborn child.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide.
Unsuitable extinguishing media	: Water.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: Static discharge may serve as an ignition source for this product.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

General measures	: Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8). Avoid vapor formation. In case of spills, beware of slippery floors and surfaces. Eliminate all sources of ignition.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear Protective equipment as described in Section 8.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.
----------------------	---

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
-----------------	--

Wilsonart® 110 Adhesive Solvent

Methods for cleaning up : Remove all sources of ignition. Avoid breathing of vapors. Wear appropriate respirator and other protective clothing. Ventilate. Shut off source of leak only if safe to do so. Soak up with absorbent material, and place in non-leaking containers for proper disposal.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, sparks and open flames. Use adequate ventilation and avoid repeated or prolonged skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Ground/bond container and receiving equipment. Prohibit smoking in storage area.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep container tightly closed. Isolate from oxidizers, heat, sparks, electrical equipment and open flame. Closed containers may explode if exposed to extreme heat. Store in a cool dry place. Prohibit smoking in storage area. Do not store with acids or oxidizers. Electrical service in storage area must be rated for flammable liquids.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Distillates, petroleum, light distillate hydrotreating process, low-boiling (68410-97-9)

Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

Toluene (108-88-3)

ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	Visual impair; female repro;

Acetone (67-64-1)

ACGIH TWA (ppm)	500 ppm
ACGIH STEL (ppm)	750 ppm
OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
OSHA PEL (TWA) (ppm)	1000 ppm
OSHA PEL (STEL) (mg/m ³)	2400 mg/m ³ (The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors)
OSHA PEL (STEL) (ppm)	1000 ppm

Cyclohexane (110-82-7)	
ACGIH TWA (ppm)	100 ppm
OSHA PEL (TWA) (mg/m ³)	1050 mg/m ³
OSHA PEL (TWA) (ppm)	300 ppm

Isopentane (78-78-4)	
ACGIH TWA (ppm)	600 ppm (listed under Pentane, all isomers)
Remark (OSHA)	OELs not established

Pentane (109-66-0)	
ACGIH TWA (ppm)	600 ppm (listed under Pentane, all isomers)
OSHA PEL (TWA) (mg/m ³)	2950 mg/m ³
OSHA PEL (TWA) (ppm)	1000 ppm

Naphtha, petroleum, hydrotreated light (64742-49-0)	
Remark (ACGIH)	OELs not established
Remark (OSHA)	OELs not established

Hexane (110-54-3)	
ACGIH TWA (ppm)	50 ppm
OSHA PEL (TWA) (mg/m ³)	1800 mg/m ³
OSHA PEL (TWA) (ppm)	500 ppm

8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Safety glasses. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl.

Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles.

Wilsonart® 110 Adhesive Solvent

Skin and body protection	: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.
Respiratory protection	: Wear a NIOSH-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions. In case of inadequate ventilation or risk of inhalation of vapors, use suitable respiratory equipment with gas filter (type A2). Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	: Liquid
Appearance	: Clear liquid.
Color	: No data available
Odor	: Solvent.
Odor Threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: 6.1 Weighted Average is 6.1 (Highest Component is 7.7 - Acetone)
Melting point	: -94.5 °C May start to solidify based on Toluene (-138 °F)
Freezing point	: No data available
Boiling point	: 56 °C (132 °F)
Flash point	: -14.7 °C Closed Cup (5.5 °F)
Auto-ignition temperature	: 225 °C for lowest known component - Light Hydrotreated Distillate (437 °F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 250 mm Hg at 20 °C (calculated)
Relative vapour density at 20 °C	: 2.73 Air=1 (Weighted average) Highest component is 3.14 - Toluene
Relative density	: No data available
Density	: 6.26 lb/gal
Solubility	: Water: Not soluble in water
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 2 - 13 vol %

9.2. Other information

VOC content : 735 g/l
Other properties : Percent Volatile: 100%.
Additional information : VHAP Calculated: 1.52 lbs/gal or 182 g/L

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Heat, flame. Ignition sources.

10.5. Incompatible materials

Strong acids and alkalies, oxidizing agents, reducing agents, copper and copper alloys.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Various hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h

Acetone (67-64-1)	
LC50 inhalation rat (mg/l)	50100 mg/m ³

Cyclohexane (110-82-7)	
LD50 oral rat	12705 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	13.9 mg/l/4h

Isopentane (78-78-4)	
LC50 inhalation rat (mg/l)	280000 mg/m ³ 4 h

Wilsonart® 110 Adhesive Solvent

Pentane (109-66-0)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	364 g/m ³ 4 h

Naphtha, petroleum, hydrotreated light (64742-49-0)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (ppm)	73680 ppm/4h

Hexane (110-54-3)	
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (ppm)	48000 ppm/4h

Skin corrosion/irritation : Causes skin irritation.
 Serious eye damage/irritation : Causes serious eye irritation.
 Respiratory or skin sensitisation : Not classified
 Germ cell mutagenicity : Not classified.
 Carcinogenicity : Not classified.

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility. Suspected of damaging the unborn child.
 Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.
 Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.
 Aspiration hazard : May be fatal if swallowed and enters airways.
 Symptoms/injuries after inhalation : May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.
 Symptoms/injuries after skin contact : Causes skin irritation.
 Symptoms/injuries after eye contact : Causes serious eye irritation.
 Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.
 Chronic symptoms : Causes damage to organs through prolonged or repeated exposure. Suspected of damaging fertility. Suspected of damaging the unborn child.

SECTION 12: Ecological information
12.1. Toxicity

Ecology - general : No data available.

Wilsonart® 110 Adhesive Solvent

Hexane (110-54-3)	
LC50 fishes 1	2.1 - 2.98 mg/l 96 Hr LC50 Pimephales promelas [flow-through]

12.2. Persistence and degradability

110 Adhesive Solvent	
Persistence and degradability	The product is not biodegradable.

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities. No discharge to surface waters is allowed without an NPDES permit.
- Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

- Transport document description : UN1993 Flammable liquids, n.o.s. (contains: Light petroleum distillate), 3, II
- UN-No.(DOT) : 1993
- DOT NA no. : UN1993
- Proper Shipping Name (DOT) : Flammable liquids, n.o.s.
- Department of Transportation (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
- Hazard Classes : 3 - Flammable liquid
- Hazard labels (DOT) : 3 - Flammable liquid



- Packing group (DOT) : II - Medium Danger
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

Wilsonart® 110 Adhesive Solvent

DOT Vessel Stowage Location : B - (i) The material may be stowed “on deck” or “under deck” on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) “On deck only” on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Additional information

Other information : **Limited Quantity Exception**-flammable liquids in Packing Group II, inner packagings not over 1.0 L (0.3 gallons) net capacity each, packed in a strong outer packaging.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

110 Adhesive Solvent	
All components of this product are listed on the TSCA Inventory or are exempt	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard
	CAS #: 108-88-3 (Toluene)
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	1000 lb
Section 313	Listed on US SARA section 313
	CAS #: 67-64-1 (Acetone)
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	5000 lb
Section 313	Not Listed
	CAS #: 110-54-3 (Hexane)
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	5000 lb
Section 313	Listed on US SARA section 313
	CAS #: 110-82-7 (Cyclohexane)
Section 302 (EHS) TPQ	lb
Section 304 EHS RQ	lb
CERCLA RQ	1000 lb

Wilsonart® 110 Adhesive Solvent

110 Adhesive Solvent	
Section 313	Listed on US SARA section 313

15.2. International regulations

No additional information available.

15.3. US State regulations
California Proposition 65

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

Toluene (108-88-3)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	

Benzene (71-43-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	Yes	No	Yes	

Ethylbenzene (100-41-4)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

Toluene (108-88-3)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List U.S. - Pennsylvania - RTK (Right to Know) List

Acetone (67-64-1)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Cyclohexane (110-82-7)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

Wilsonart® 110 Adhesive Solvent


Isopentane (78-78-4)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Pentane (109-66-0)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Hexane (110-54-3)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

- NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.
- NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

- Health : 3*
- Flammability : 4
- Physical : 0
- Personal Protection :

Changes to this Revision: Revise to GHS requirements.

Prepared By: Environmental, Health, and Safety Department, Wilsonart LLC.
 Telephone: 254-207-7000
 Internet: www.wilsonart.com

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named manufacturer nor any of its subsidiaries assumes any liability whatsoever for accuracy or completeness of the information contained herein.
Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.